

16-PORT FIBER TERMINATION BOX



This IP65 distribution box offers the ability to terminate 16 fibers housed in a robust ABS enclosure for indoor and outdoor applications. With the ability to use a full array of adapter types offering a flexible solution to the end user, enabling them to incorporate a multi functional enclosure which allows easy access during installation or re-work with no disturbance of the existing cable or fibers. In addition to the array of adaptors the enclosure also offers up to 16 exit points for drop cables and 2 standard cable entry points for loose tube, tight buffer, pre terminated and steel tape armoured cable. Each enclosure has integrated strength member tie positions and bend radius protection with the addition of a removable front door allowing for quick and easy installation.

★ Features

- Up to 16 fibers
- Hinged splice tray for easy installation
- Multiple adapter options available
- 16 adapter positions
- IP 65
- Accepts loose tube, distribution and pre terminated cables
- Integrated bend radius protection
- Rubber inserts for up to 16 drop cables
- ROHS, REACH SvHC
- Supplied with 16 heatshrink splice protectors
- Supplied with transit tubing
- Supplied with wall fixings

⚙️ Technical Specification

Height	320mm
Width	260mm
Depth	100mm
Net weight	1.17kg
IP rating	IP65
Suitable for adapter type	SC Simplex LC Duplex
Number of fibers	16
Number of ports	16
Cable entry 20mm	2
Cable exit 10mm	16
Material	ABS
ABS Colour	White
Operating temperature	-40oC to +50oC
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1
Compliant to	RoHS, Reach/SVHC

✓ Applications

- Data centres, premise installations, telecommunication networks
- Ethernet, Fiber Channel, ATM, LAN, MAN and WAN
- Data communication and telecommunication networks
- Indoor applications

🛒 Ordering Information

Description	Part No.
IP65 Indoor/Outdoor Distribution Box Supports Up To 16 Fibers	SWB17