

# FIBER WALL SOCKET

## SINGLE OR DUAL FIBERS



The compact fiber wall socket supplied by FIBER-REX is designed for residential and business applications and holds up to four fiber terminations. This wall box enables the installation of either a single Sirocco Blown Tube cables using up to a 2 fiber blown unit or two 2 fiber ruggedized cables to be spliced to 2 SC pigtails (PC or APC). The pigtails would which connect to adapters at the base of the unit. This box has a transparent plastic cover on the front adapter side, providing substantial protection to the installed fibers.

The unit can be quickly installed within an office, house or communication room environment.

### ★ Features

- SC simplex and duplex adapter
- Ergonomic design
- Ability to allow cables to enter from rear or bottom of the unit
- 30mm minimum bend radius
- Flip tray to allow access to pigtails and cable entry
- Removable cover for easy access
- Unit manufactured from fire resistant UL94-V0 rated material
- Standard white color

### ✓ Applications

- FTTx networks
- Data communication networks
- Indoor applications

### ⚙️ Technical Specification

Parameter	Value
Width	86mm
Height	86mm
Depth	25mm
Number of Ports	1, 2
Max. Splicing Capacity	2 Splices
Suitable Adapter Type	SC Simplex, SC Duplex
Number of Cable Entry	2
Material	PC+ABS
Operating Temperature	-40°C to +50°C
Color	White
Compliant to	RoHS, REACH, SvHC

### 🛒 Ordering Information

Part No.	Description
SFTH01	Fiber Wall Socket