WALL MOUNT RACK



STANDARD UNIT OF 19" RACK

♠ Features

- Vented top & bottom cover
- Rack framework
- 1 front Perspex (Acrylic) door with lock (with Frame)
- 2 detachable panel mounting members
- 1 row power points
- Cable with plug top
- 20 sets of M6 caged nuts
- Epoxy high quality powder coated finishing (Black Colour)

Technical Specification

Model			Overall Height	Internal Height	Power Outlet	Weight (kg)	
Size	400mm D	5000mm D	600mm D	[mm]	(mm)	(13AMP)	500mm D
6U x 19"	WM0664	WM0665	WM0666	337	267	3 Socket	17
9U x 19"	WM0964	WM0965	WM0966	470	400	3 Socket	20
12U x 19"	WM1264	WM1265	WM1266	603	533	3 Socket	23
15U x 19"	WM1565	WM1565	WM1566	737	667	3 Socket	26
18U x 19"	WM1864	WM1865	WM1866	870	800	3 Socket	29

2-POST OPEN FRAME RACK

The Primestar 2 post Open Rack offer a quality solution for the economical installation of rack-mountable networking equipment. The 2-Post Rack offers cost conscious customers a simple solution for mack mounting network equipment in a secure managed environment including data centers, wiring closets and co-location facilities.



Model	Product Code	Overall Height (mm)	
42U	20R4200	2037	
46U 20R4600		2215	





2-POST WITH TRUNKING FOR CABLE MANAGEMENT

The Primestar 2 post Open Rack with Trunking offers a quality cable management solution for the installation of networking installation.

Technical Specification

Model	Product Code	Overall Height (mm)	
42U	2TOR4200	2037	
46U	2TOR4600	2215	